



1 PREPARE 2 TREAT 3 MAINTAIN

EXTERIOR WASH-IN OIL



For oiled wood

For cleaning and care of oiled outdoor wood surfaces, e.g. patios and garden furniture.



3 in 1 oil soap

Cleans, oils and maintains wood surfaces simultaneously. Helps postpone re-oiling.



Increases resistance

Adds extra oil to the surface and increases the resistance of wood to wind and weather. Extends the lifetime of the wood.

APPLICATION AREA

Exterior Wash-in Oil is used for cleaning and care of oiled outdoor surfaces, such as wooden patios and garden furniture. It is a 3 in 1 product that cleans, oils and maintains wooden surfaces at the same time.

RESULT

Exterior Wash-in Oil is a mild oil soap that adds extra oil to the surface, penetrating the wood and providing additional protection for up to 6 weeks. Occasional use can postpone the next proper re-oiling of the surface.

Product information

Coverage: 861-1076 sq. ft./L
Packaging: 1 L and 2.5 L



HOW TO...

...MAINTAIN OILED OUTDOOR WOOD

Tools

The oil soap is preferably applied with a soft brush or swabber.

Preparation

The surface must be free of grime, grease and growth (moss, algae etc).

If the wood is very dirty with grime and green growth, we recommend that the surface is cleaned with WOCA Exterior Wood Cleaner before it is treated with Exterior Wash-in Oil.

Maintenance and cleaning

For better results, retreat the surface every 4-6 weeks with Exterior Wash-in Oil to retain the beautiful look of the wood and to postpone the next proper re-oiling.

Risk of self-ignition!

Any cloths that have been soaked in oil should be stored/ disposed of in sealed containers or incinerated due to risk of self-ignition.



INSTRUCTIONS

- 1 Mix Exterior Wash-in Oil with clean water in a mixture ratio of 1:10.

Please note:

The oil soap will change from having an oily consistency, to a milk-coloured, aqueous mixture.

- 2 Apply Exterior Wash-in Oil with a soft brush or swabber and work the oil soap right into the wood.
- 3 Leave the mixture to stand for 10 minutes before rinsing off excess oil soap with clean water.
- 4 Leave the surface to dry before use.