



1 PREPARE 2 TREAT 3 MAINTAIN

# HARDWAX OIL EXTREME

## APPLICATION AREA

Hardwax Oil Extreme is for untreated, new or newly-sanded wooden surfaces.

It can also be used as a topcoat on top of WOCA Master Colour Oil.

## RESULT

Hardwax Oil Extreme ensures an extremely robust and resistant surface that is well-protected against spills and stains.

The oil emphasises the natural glow of the wood, leaving a comfortable anti-slip surface that is easy to maintain.

## Product information

Coverage: 215 SF/L  
Packaging: 0.75 and 2.5 L  
Available in Natural and White



resistance

### Extreme resistance

Very robust surface with extremely high resistance to spills, stains, marks and scratches.



tool

### Buffer

Efficient and effective method.



appearance

### Natural appearance

Gives the wood a natural appearance and breathable surface.



maintenance

### Easy to maintain

No special tools required. Just use the standard WOCA system.





# HOW TO...

## ...DO THE BASIC TREATMENT OF WOODEN FLOORS

### Tools

- Either polishing machine or doodlebug for the manual finishing
- Paint roller and cotton cloths
- Clean tools with WOCA Solvent

### Preparation

The floor must be free of dirt, grease, wax and sanding residue. Previously treated floors should be sanded down to bare wood with grit 120-150. Vacuum thoroughly and wipe the floor down afterwards if necessary, using a tightly-wrung water-soaked cloth.




It is important that the product, the room and the floor are at a temperature between 59°F and 86°F and that air humidity is approx. 50%. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time.

### Please note

Do not expose the floor to water or clean it for the first 7 days, while the oil is hardening.

### Maintenance and cleaning

For the cleaning, we recommend using WOCA Natural Soap or WOCA Oil Refreshing Soap, and for the maintenance we recommend WOCA Oil Care. Re-oil with Hardwax Oil Extreme or WOCA Maintenance Gel as required.



## INSTRUCTIONS

- 1 Wash the floor with WOCA Intensive Wood Cleaner. Leave the floor to dry for at least 8 hours before applying the oil.
- 2 Hardwax Oil Extreme should be stirred thoroughly before and during use. Containers with different batch numbers should be mixed to avoid colour mismatch. Apply a thin and even coat of oil with a short-bristled paint roller (3/16" nap) to a small area of the floor at a time (50-100 SF). Distribute the oil thoroughly.
- 3 Leave the oil to stand on the surface for 5-10 minutes, while shiny. If the oil soaks quickly into the wood, apply more oil.  
**Please note:** After approx. 15 minutes, Hardwax Oil Extreme will begin to seal on the surface.
- 4 Buff the surface with a white or beige buffer pad until the wood appears saturated. Then buff with a clean lint-free cotton cloth to remove excess oil before proceeding to the next section. The surface should not appear wet and no excess oil should remain on the surface.
- 5 Leave the floor to dry for 8-10 hours. Drying time will vary by temperature, humidity and application quantity. Lower temperatures and/or higher humidity can extend drying time.
- 6 Repeat steps 2-4 if a second layer of oil is required or if you want a higher gloss or tougher surface. A single coat of oil is normally enough for previously-oiled surfaces.
- 7 The newly-oiled floor can be used with caution the following day.
- 8 Clean tools with WOCA Solvent.